

CURRENT SENSOR CAPACITY INCREASE IMPROVEMENT

Marcel Valoria
Jeremy Baltazar
Erwell Labay

Operations Engineering, Assembly Production, Maintenance and Logistics
Allegro Microsystems Philippines Inc.
4756 Sampaguita Street Marimar Village Brgy. Sun Valley Parañaque City, Philippines
mvaloria@allegromicro.com, jbaltazar@allegromicro.com, elabay@allegromicro.com

ABSTRACT

Assembly Manufacturing in Allegro Microsystems Philippines Inc. is always working on the capacity improvement in the line. The team had checked on what package needed attention to resolve the ongoing increase in volume requirements. Based on the capacity profiles, Current Sensor has the highest critical capacity starting from September 2023 onwards given the target volume of 700K. Based on the data it's already beyond the 94% which IE already tagged this as critical level. Stations with low capacity are coming from Overmold and MTFS station.

For us to effectively resolve and come up with the solutions we used Lean tools and methodologies, such as Pareto Charts, Process Mapping, Spaghetti Diagrams, Pain Points and Gemba Walk. Utilization of these tools and methodologies help us get through to the heart of the issue and come up with effective solutions or improvements to cater to the current problem that we have, which is the low capacity.

In our Pain Points checking, we found out what were the causes of the concerns and what affects the low capacity of the two stations. We have identified several downtimes that directly affect the output and utilization of our machines. There were downtimes contributed mainly by production and some activities coming from maintenance.

After the team classified the cause for the low capacity of the declared stations, our team instantly works on the needed improvements or counter measures.

Improvements or countermeasures were made since the Lean execution, and these were sustained by the team. Thus, the improvement has been standardized and documented. Significant improvements were implemented and noticed positive outcome. Such as

- a.) Overmold capacity increase from 571K to 606K or 6.21% capacity improvement
- b.) Overmold machine utilization increase to 1.83%
- c.) MTFS Capacity increase from 673K to 715K or 6.27K capacity improvement
- d.) MTFS UPH increase to 3.13%
- e.) MTFS machine utilization increase to 3.04%
- f.) Total Projected annual savings approximately Php 600K
- f.) FY25 possible annual gain in capacity increase PhP 771K to PhP 919K

1. 0 INTRODUCTION

1.1 Background of the Study

Our company's theme for this Fiscal year is "One degree at a time", Allegro Microsystems Philippines upholds its commitment to continuously improve in all aspects and this includes the Improvement in capacity.

Based on the IE capacity profiles, Current Sensor has the highest critical capacity starting from September 2023 onwards given the target volume of 700K. (Fig 1)




Fig. 1. OE Capacity Profile showing CS as the critical package

CS Machine Capacity vs Volume Requirement- Among the four CS Stations, Overmold and MTFs have the lowest capacity.

To support our Current Sensor target capacity of 700K, we need to work out the capacity of the two stations where Overmold and MTFs are bottleneck stations. (See Fig. 2) Current Overmold capacity is at 571K, a gap of 129k. Current MTFs capacity is at 673k, a gap of 27k.




Fig. 2. Overmold and MTFs Stations with the Lowest Capacity at CS

Based on Pareto Diagram for overmold as shown on Fig 3, the highest downtime contributory is the planned downtime. Breaking this down for the planned downtime, production has the highest downtime with 26.33% contribution. Production downtimes were mainly due to Wait qual, Scheduled cleaning, In qual and Breaktime. These were the activities that contributed to the low utilization and eventually lower the capacity of overmold machines.




Fig. 3. – CS Mold Utilization data Pareto Diagram

On the other hand, Pareto Diagram for MTFs as shown on Fig 4, the highest downtime contributory is the planned downtime. Breaking this down, production has the highest downtime with 10.42% contribution. Downtime from production was contributed by set up production, wait qual, In qual and breaktime. Also, for maintenance, it's more on the machine cleaning. These are the activities that impacted

the utilization and eventually lower the capacity of MTFs machines.




Fig. 4. – CS MTFs Utilization Data Pareto Diagram

1.2 Objective

Our goal on this project is to increase our Current Sensor Capacity, especially in the two stations with the lowest capacity profile. Our drive is to increase Overmold capacity from 571K to 641K by Sept 2023, hitting 54% of the gap or a 10.9% increase in capacity. Also to increase MTFs capacity from 673K to 700K by Sept 2023, hitting 100% of the gap or a 4% increase in capacity

1.3 Scope

The scope of the project will cover Overmold and MTFs stations only.

2.0 REVIEW OF RELATED WORK – NOT APPLICABLE

3.0 METHODOLOGY

Our team used several Lean methodologies to pinpoint the problem and work out possible improvements. We did the Gemba walk and from there, we performed process mapping pain points and brainstorming. With these activities, we are able to determine the root cause of the problem.



Fig. 5. – Different Lean Methodology

3.1 Root Cause Determination

Using Pain Points to determine the problem (Fig 6) the team identified four possible causes of low capacity of Overmold station. Identified problem or pain points here are (1) Long Mold cleaning material preparation, (2) Long cleaning time duration (3) Long duration of machine qualification (4) Under-utilized machines due to breaktime without staggered support




Fig. 6 – Pain Points Diagram for Overmold Station

Using the same tools for determining the problem at MTFs (Fig 7), the team identified four possible causes of low capacity at this station. Identified problems were (1) Frequent transferring of Trays to Empty tray racks & improper stacking at pushcart handlebar, (2) The number of sample size during regular visual monitoring is 5 tubes (170 units), this done every 30 mins (6X per lot) which is 2.5X more to the required sample size stated in SPE-0000144. (3) During start of shift machine qualification, the machine stays idle until the inspection of qualification samples is completed (4) Current PLC sensor delay settings is 100 mm/s causing the Trim Singulation tool to be idle for 6 sec per strip.




Fig. 7 – Pain points Diagram for MTFs Station

3.1 Root Cause Improvements

Based on the identified problems, the team created improvements that could help resolve identified root causes.


Table 1. Overmold Problem and Improvement Actions

No.	Problem	Improvement
1	Long Material Preparation time for Mold Cleaning	Provide proper locations and labels on worktable for needed materials & implement advanced preparation of materials – to be done by previous shift operator
2	Long mold cleaning time which consumes average of 1.6 hours or 96 mins per cleaning.	Reduce set curing cycle time parameters to minimum allowable time
3	Under-utilized machines due to breaktime without staggered support	Utilize multi-function and execute additional multi operators at Overmold.

(1) Improved work table



(2) Curing time set to minimum



(3) Allocate staggered opr

Overmold Certified Operators	For Molds at Overmold
Operator A	Operator B
Operator C	Operator D
Operator E	Operator F
Operator G	Operator H
Operator I	Operator J
Operator K	Operator L
Operator M	Operator N
Operator O	Operator P
Operator Q	Operator R
Operator S	Operator T
Operator U	Operator V
Operator W	Operator X
Operator Y	Operator Z
Operator AA	Operator AB
Operator AC	Operator AD
Operator AE	Operator AF
Operator AG	Operator AH
Operator AI	Operator AJ
Operator AK	Operator AL
Operator AM	Operator AN
Operator AO	Operator AP
Operator AQ	Operator AR
Operator AS	Operator AT
Operator AU	Operator AV
Operator AW	Operator AX
Operator AY	Operator AZ
Operator BA	Operator BB
Operator BC	Operator BD
Operator BE	Operator BF
Operator BG	Operator BH
Operator BI	Operator BJ
Operator BK	Operator BL
Operator BM	Operator BN
Operator BO	Operator BP
Operator BQ	Operator BR
Operator BS	Operator BT
Operator BU	Operator BV
Operator BW	Operator BX
Operator BY	Operator BZ
Operator CA	Operator CB
Operator CC	Operator CD
Operator CE	Operator CF
Operator CG	Operator CH
Operator CI	Operator CJ
Operator CK	Operator CL
Operator CM	Operator CN
Operator CO	Operator CP
Operator CQ	Operator CR
Operator CS	Operator CT
Operator CU	Operator CV
Operator CW	Operator CX
Operator CY	Operator CZ
Operator DA	Operator DB
Operator DC	Operator DD
Operator DE	Operator DF
Operator DG	Operator DH
Operator DI	Operator DJ
Operator DK	Operator DL
Operator DM	Operator DN
Operator DO	Operator DP
Operator DQ	Operator DR
Operator DS	Operator DT
Operator DU	Operator DV
Operator DW	Operator DX
Operator DY	Operator DZ
Operator EA	Operator EB
Operator EC	Operator ED
Operator EE	Operator EF
Operator EG	Operator EH
Operator EI	Operator EJ
Operator EK	Operator EL
Operator EM	Operator EN
Operator EO	Operator EP
Operator EQ	Operator ER
Operator ES	Operator ET
Operator EU	Operator EV
Operator EW	Operator EX
Operator EY	Operator EZ
Operator FA	Operator FB
Operator FC	Operator FD
Operator FE	Operator FF
Operator FG	Operator FH
Operator FI	Operator FJ
Operator FK	Operator FL
Operator FM	Operator FN
Operator FO	Operator FP
Operator FQ	Operator FR
Operator FS	Operator FT
Operator FU	Operator FV
Operator FW	Operator FX
Operator FY	Operator FZ
Operator GA	Operator GB
Operator GC	Operator GD
Operator GE	Operator GE
Operator GG	Operator GH
Operator GI	Operator GI
Operator GK	Operator GL
Operator GM	Operator GM
Operator GO	Operator GO
Operator GQ	Operator GR
Operator GS	Operator GT
Operator GU	Operator GV
Operator GW	Operator GX
Operator GY	Operator GZ
Operator HA	Operator HB
Operator HC	Operator HC
Operator HE	Operator HE
Operator HG	Operator HG
Operator HI	Operator HI
Operator HK	Operator HK
Operator HM	Operator HM
Operator HO	Operator HO
Operator HQ	Operator HQ
Operator HS	Operator HS
Operator HU	Operator HU
Operator HW	Operator HW
Operator HY	Operator HY
Operator IA	Operator IA
Operator IC	Operator IC
Operator IE	Operator IE
Operator IG	Operator IG
Operator II	Operator II
Operator IK	Operator IK
Operator IM	Operator IM
Operator IO	Operator IO
Operator IQ	Operator IQ
Operator IS	Operator IS
Operator IU	Operator IU
Operator IW	Operator IW
Operator IY	Operator IY
Operator JA	Operator JA
Operator JC	Operator JC
Operator JE	Operator JE
Operator JG	Operator JG
Operator JI	Operator JI
Operator JK	Operator JK
Operator JM	Operator JM
Operator JO	Operator JO
Operator JQ	Operator JQ
Operator JS	Operator JS
Operator JU	Operator JU
Operator JW	Operator JW
Operator JY	Operator JY
Operator KA	Operator KA
Operator KC	Operator KC
Operator KE	Operator KE
Operator KG	Operator KG
Operator KI	Operator KI
Operator KK	Operator KK
Operator KM	Operator KM
Operator KO	Operator KO
Operator KQ	Operator KQ
Operator KS	Operator KS
Operator KU	Operator KU
Operator KW	Operator KW
Operator KY	Operator KY
Operator LA	Operator LA
Operator LC	Operator LC
Operator LE	Operator LE
Operator LG	Operator LG
Operator LI	Operator LI
Operator LK	Operator LK
Operator LM	Operator LM
Operator LO	Operator LO
Operator LQ	Operator LQ
Operator LS	Operator LS
Operator LU	Operator LU
Operator LW	Operator LW
Operator LY	Operator LY
Operator MA	Operator MA
Operator MC	Operator MC
Operator ME	Operator ME
Operator MG	Operator MG
Operator MI	Operator MI
Operator MK	Operator MK
Operator MM	Operator MM
Operator MO	Operator MO
Operator MQ	Operator MQ
Operator MS	Operator MS
Operator MU	Operator MU
Operator MW	Operator MW
Operator MY	Operator MY
Operator NA	Operator NA
Operator NC	Operator NC
Operator NE	Operator NE
Operator NG	Operator NG
Operator NI	Operator NI
Operator NK	Operator NK
Operator NM	Operator NM
Operator NO	Operator NO
Operator NQ	Operator NQ
Operator NS	Operator NS
Operator NU	Operator NU
Operator NW	Operator NW
Operator NY	Operator NY
Operator OA	Operator OA
Operator OC	Operator OC
Operator OE	Operator OE
Operator OG	Operator OG
Operator OI	Operator OI
Operator OK	Operator OK
Operator OM	Operator OM
Operator ON	Operator ON
Operator OQ	Operator OQ
Operator OS	Operator OS
Operator OU	Operator OU
Operator OW	Operator OW
Operator OY	Operator OY
Operator PA	Operator PA
Operator PC	Operator PC
Operator PE	Operator PE
Operator PG	Operator PG
Operator PI	Operator PI
Operator PK	Operator PK
Operator PM	Operator PM
Operator PO	Operator PO
Operator PQ	Operator PQ
Operator PS	Operator PS
Operator PU	Operator PU
Operator PW	Operator PW
Operator PY	Operator PY
Operator QA	Operator QA
Operator QC	Operator QC
Operator QE	Operator QE
Operator QG	Operator QG
Operator QI	Operator QI
Operator QK	Operator QK
Operator QM	Operator QM
Operator QO	Operator QO
Operator QQ	Operator QQ
Operator QS	Operator QS
Operator QU	Operator QU
Operator QW	Operator QW
Operator QY	Operator QY
Operator RA	Operator RA
Operator RC	Operator RC
Operator RE	Operator RE
Operator RG	Operator RG
Operator RI	Operator RI
Operator RK	Operator RK
Operator RM	Operator RM
Operator RO	Operator RO
Operator RQ	Operator RQ
Operator RS	Operator RS
Operator RU	Operator RU
Operator RW	Operator RW
Operator RY	Operator RY
Operator SA	Operator SA
Operator SC	Operator SC
Operator SE	Operator SE
Operator SG	Operator SG
Operator SI	Operator SI
Operator SK	Operator SK
Operator SM	Operator SM
Operator SO	Operator SO
Operator SQ	Operator SQ
Operator SS	Operator SS
Operator SU	Operator SU
Operator SW	Operator SW
Operator SY	Operator SY
Operator TA	Operator TA
Operator TC	Operator TC
Operator TE	Operator TE
Operator TG	Operator TG
Operator TI	Operator TI
Operator TK	Operator TK
Operator TM	Operator TM
Operator TO	Operator TO
Operator TQ	Operator TQ
Operator TS	Operator TS
Operator TU	Operator TU
Operator TW	Operator TW
Operator TY	Operator TY
Operator UA	Operator UA
Operator UC	Operator UC
Operator UE	Operator UE
Operator UG	Operator UG
Operator UI	Operator UI
Operator UK	Operator UK
Operator UM	Operator UM
Operator UN	Operator UN
Operator UQ	Operator UQ
Operator US	Operator US
Operator UU	Operator UU
Operator UW	Operator UW
Operator UY	Operator UY
Operator VA	Operator VA
Operator VC	Operator VC
Operator VE	Operator VE
Operator VG	Operator VG
Operator VI	Operator VI
Operator VK	Operator VK
Operator VM	Operator VM
Operator VO	Operator VO
Operator VQ	Operator VQ
Operator VS	Operator VS
Operator VU	Operator VU
Operator VW	Operator VW
Operator VY	Operator VY
Operator WA	Operator WA
Operator WC	Operator WC
Operator WE	Operator WE
Operator WG	Operator WG
Operator WI	Operator WI
Operator WK	Operator WK
Operator WM	Operator WM
Operator WO	Operator WO
Operator WQ	Operator WQ
Operator WS	Operator WS
Operator WU	Operator WU
Operator WW	Operator WW
Operator WY	Operator WY
Operator XA	Operator XA
Operator XC	Operator XC
Operator XE	Operator XE
Operator XG	Operator XG
Operator XI	Operator XI
Operator XK	Operator XK
Operator XM	Operator XM
Operator XO	Operator XO
Operator XQ	Operator XQ
Operator XS	Operator XS
Operator XU	Operator XU
Operator XW	Operator XW
Operator XY	Operator XY
Operator YA	Operator YA
Operator YC	Operator YC
Operator YE	Operator YE
Operator YG	Operator YG
Operator YI	Operator YI
Operator YK	Operator YK
Operator YM	Operator YM
Operator YO	Operator YO
Operator YQ	Operator YQ
Operator YS	Operator YS
Operator YU	Operator YU
Operator YW	Operator YW
Operator YY	Operator YY
Operator ZA	Operator ZA
Operator ZC	Operator ZC
Operator ZE	Operator ZE
Operator ZG	Operator ZG
Operator ZI	Operator ZI
Operator ZK	Operator ZK
Operator ZM	Operator ZM
Operator ZO	Operator ZO
Operator ZQ	Operator ZQ
Operator ZS	Operator ZS
Operator ZU	Operator ZU
Operator ZW	Operator ZW
Operator ZY	Operator ZY

Fig. 8 – Kaizen actions for Low Capacity at Overmold

Table 2. MTFs Problem and Improvement Actions

No.	Problem	Improvement
1	Frequent transferring of Trays to Empty tray racks & improper stacking at pushcart handlebar	Provide additional layer on the existing current sensor pushcart where the empty trays will be place while waiting for the in-process lot be move out
2	The number of sample size during regular visual monitoring is 5 tubes (170 units), this done every 30 mins (6X per lot) which is 2.5X more to the required sample size stated in SPE-0000144.	Re-align the sample size based on guidelines stated in SPE-0000144 to 204 units
3	During start of shift machine qualification, the machine stays idle until the inspection of qualification samples was completed	Remove waiting time by implementing no waiting of qualification result Requirement: Machine should be in running condition during shift transition

4	Current PLC sensor delay settings is 100 mm/s causing the Trim Singulation tool to wait with 6 sec per strip.	Optimized sensor delay settings of lead frame pusher and pick and place which results increase in UPH
---	---	---




Fig. 9 – Kaizen actions for Low-capacity issue at MTFS

4.0 RESULTS AND DISCUSSION

The end of mind of this project is to improve the capacity of the current sensor line.

With the team's collaboration of ideas and hard work, the team managed to improve the Overmold and MTFS capacity. Overmold capacity increase from 571K to 606K or 6.21% capacity improvement and its utilization increase to 1.83%. (Fig 10)

MTFS Capacity increase from 673K to 715K or 6.27K capacity improvement. UPH also increased to 3.13% and machine utilization increased to 3.04%. (Fig. 11)

Total Projected annual savings approximately Php 600K and FY25 possible annual gain in capacity increase Php 771K to Php 919K. (Fig. 12)




Fig. 10 – Overmold Capacity Improvement after Kaizen Result




Fig 11 – MTFS Capacity improvement after Kaizen Result

Financial Benefits: Cost Savings and Capacity Gains

Item Number	Original Cost	New Cost	Inc (Dec)	FY25 Volume	Total \$	Total PHP
CS-348-SEN-TRANS	\$ 0.33238	\$ 0.33151	\$ (0.000869)	10,727,418	\$ (9,326.42)	(\$17,383.37)
CS-368-SEN-TRANS	\$ 0.33238	\$ 0.33151	\$ (0.000869)	1,696,728	\$ (1,476.87)	(\$1,929.35)
Total Projected savings					\$ (10,803.30)	(\$9,312.72)

FY25 Possible gains from incr in capacity	Overmold	MTFS
Resource code	OMOLDIAUR	TRNGYKCS
Current Capacity	35,029,614.75	29,710,152.63
Validated Capacity	37,226,649.20	31,555,241.96
Incr in Capacity	2,197,034.45	1,845,089.33
Annual Gain (USD)	\$ 13,900.62	\$ 16,571.51
Annual Gain (PHP)	771,136.98	919,304.33

Total Projected Annual Savings Approximately Php600K

FY25 Possible Annual Gain in Capacity Increase Php771K to Php919K

Fig. 12. – Financial Benefits after Kaizen Results

5.0 CONCLUSION

Through this project, the team were able to conclude that OVERMOLD and MTFS low utilization are the main factor why we have LOW CAPACITY for Current Sensor.

Machine capacity increased through chopping down and eliminating some of the downtime and working on machine improvement.

This Kaizen project resulted in adding up CS capacity specifically, at Overmold and MTFS. (Fig 13) This project had contributed to our Financial advantage since it brought Cost Savings and Capacity Gains. Total projected savings are approximately Php 600,000.




Fig. 13. – Improved Capacity after Kaizen

6.0 RECOMMENDATIONS

It is highly recommended to apply Lean tools and methodologies used in this project such as Pareto Chart, Process Mapping, Pain points, Spaghetti Diagram, Gemba walk, Visual management and Yokoten. The same tool can help with any Capacity improvement in the company.

Fan-out all activities to applicable machines (Fig 14)




Fig. 14. – Fanning out activities in all applicable machines

7.0 ACKNOWLEDGMENT

The Authors would like to thank the following people for sharing their invaluable input for this study:

Sponsor of the Project, Section Manager, Assembly Maintenance, Rodolfo Asaytuno, our Mentor/ advisers Assembly Operations & Equipment Engineering Director Mr. Eric Roxas, Assembly Manufacturing Manager Ms. Cathie Rivas, Assembly Production Section Manager Ms. Angeli Flores, our multi-disciplinary members, Ian Mangampo, Judit Aguila, Arlan Bomediano, Marvin Demol, RJ Villanueva, Kathleen Llagas, Ramil de Leon, Manuel Estareja, Marille Benedictos and Melissa Grace Henera.

8.0 REFERENCES– NOT APPLICABLE

9.0 ABOUT THE AUTHORS



Marcel Valoria, Assembly Production Section Head with 23 years of experience in Allegro Microsystem Philippines Inc. A graduate of Electronics and Communication Technology and Bachelor of Science in Industrial Technology Major in Management at Rizal Technological University.



Jeremy Baltazar, Assembly Maintenance Lead Technician at End of Line, with 13 years of experience in Allegro Microsystem Philippines Inc. A graduate of Electronics and Communications Technology.



Erwell Labay, Senior Process Engineer of End of Line/ Current Sensor with 13 years of experience in semiconductor industry. A graduate of Bachelor of Science in Electronics and Communications Engineering at Rizal Technological University.

10.0 APPENDIX